

GH506 四层钢丝缠绕软管

EN 856 4SH



结构: 合成橡胶内层，四层高强度钢丝缠绕增强层，Dura-Tuff™ 高耐磨合成橡胶外层。

PART #	SIZE DIMENSIONS				PRESSURE				BEND		WEIGHT	
	Hose I.D.		Hose O.D. (nominal)		Working Pressure		Min. Burst Pressure		Min. Bend Radius		Weight	
	mm	in	mm	in	bar	psi	bar	psi	mm	in	kg/m	lbs/ft
GH506-12	19.1	0.75	32.3	1.27	420	6,100	1,680	24,400	280	11.00	1.49	1.00
GH506-16	25.4	1.00	38.4	1.51	420	6,100	1,680	24,400	340	13.38	2.05	1.38
GH506-20	31.8	1.25	45.5	1.79	350	5,100	1,400	20,400	460	18.11	2.54	1.71
GH506-24	38.1	1.50	53.6	2.11	300	4,350	1,200	17,400	560	22.05	3.27	2.20
GH506-32	50.8	2.00	68.1	2.68	250	3,650	1,000	14,600	700	27.56	4.58	3.08

工作温度范围: -40°C 到 +100°C (-40°F 到 +212°F)

应用:

适用于使用石油基或水基液压油的高压液压系统。如有其它特殊应用需求，请联系 Danfoss。